



FilteRx™ 6100 was developed to improve the efficiency of direct filtration processes to increase the removal of colloidal solids and to remove dissolved organics upstream of multi-media filter systems.

Features / Benefits

- Balanced blend of ferric sulfate and medium molecular weight organic polymer
- Effective when polymer-only formulations are ineffective
- Compatible with SpectraGuard™ 250 antiscalant and other phosphate-based antiscalants
- Compatible with, and with not foul, polyamide membranes
- Effective over a wide pH range

Uses

- Proven to increase efficiency of colloidal removal in direct filtration systems
- To reduce turbidity, color, and colloidal constituents from a variety of process streams
- Typical dose range 0.5 to 5.0 mg/l

Specifications

Appearance	Straw colored liquid
pH (1% solution)	2.00 - 3.00
Density (kg/liter)	1.20 - 1.40

Packaging

Pail: 5 gallon/18.9 liter

Tote: 275 gallon/1,040 liter

Drum: 55 gallon/208 liter

Bulk: available upon request

For special packaging options, please contact PWT or your local distributor.

FilteRx™ 6100
LIQUID COAGULANT BLEND OF FERRIC SULFATE AND ORGANIC POLYMER

FilterX™ 6100

LIQUID COAGULANT BLEND OF FERRIC SULFATE AND ORGANIC POLYMER

General Mixing & Application Instructions for FilterX™ 6100

1. Overdosing of coagulants may cause reduction in filtration efficiency.
2. Call Professional Water Technologies™ or your local distributor for custom chemical dosing recommendation.

NOTE: Inorganic coagulants such as FilterX™ 6100 are dependent on pH and alkalinity and their addition alters that chemistry. Please refer to the following table for further application guidelines for FilterX™ 6100.

Illustration of addition of 1 mg/l ferric sulfate.

	Formula	Mg/l alkalinity reduction	Mg/l SO ₄ increase	Mg/l Na ₂ SO ₄ increase	Mg/l CO ₂ increase	Mg/l total solids increase
Ferric Sulfate	Fe ₂ (SO ₄) ₃	0.76	0.76	1.07	0.64	0.27

NOTE: Use of incompatible antiscalants may cause a gelatinous foulant on the membrane. Please contact Professional Water Technologies™ on the proper chemical program across the entire membrane system.

ProDose XPRT™ – Scaling Prediction Software

ProDose XPRT™ provides immediate dosage capabilities for our specialty chemicals. The software can create cases to study multiple operating conditions, and directly enter concentrate analyses leading to the optimal selection of PWT product and dosage.

ProDose XPRT™ is available upon request only.

Please contact your PWT representative for more information.

The screenshot displays the PWT ProDose software interface. At the top, there is a header with the PWT logo and a navigation bar with tabs for UNITS, TEMPERATURE, PERMEATE FLOW, RECOVERY, ANTISCALANT, DOSAGE, SOURCE, PROJECT NAME, and CASE. Below this, a dashboard shows various parameters: UNITS (US), TEMPERATURE (Fahrenheit), PERMEATE FLOW (81.00), RECOVERY (75.0%), ANTISCALANT (SpectraGuard Liquid), DOSAGE (2.95 PPM), SOURCE (Well Water), PROJECT NAME (Project 1), and CASE (1). The main area is divided into several sections: PROJECT INFORMATION (CLIENT NAME: City of San Diego, PROJECT NAME: Project 1, LOCATION, PREPARED BY, DATE: 5/1/2016, WATER TYPE: Well Water), MEASUREMENTS (PRESET UNITS: CGS, Metric, U.S.; TEMPERATURE: Deg F; FLOW RATES: Gal/min; MASS UNITS: lb), COMMENTS (OPTIONAL), and TOTAL CASES (1 AVAILABLE). A table shows the case details: Case 1, Modified Date 5/27/2016. The interface also includes a sidebar with icons for PROJECT INFORMATION, WATER QUALITY, SYSTEM INFORMATION, CHEMICAL SELECTION, CALCULATIONS, and REPORT.



PWT Headquarters & Manufacturing
1048 La Mirada Court, Vista, California 92081

Toll-Free: 800.914.9072 | Direct: 760.639.4400 | Fax: 760.639.4439
Email: sales@pwtchemicals.com | www.pwtchemicals.com