



SpectraGuard™ 105 is a ready for use liquid antiscalant/dispersant that has been proven as a superior pretreatment in RO feed waters. With its ability to handle high levels of carbonate and sulfate scale, as well as low concentrations of iron and silica, SpectraGuard™ 105 ensures stable performance with complete control of the feed water chemistry.

Features / Benefits

- Phosphate-free formula reduces negative impact on the environment
- Stable molecular structure maintains integrity in high pH, high temperature and high salinity applications
- Classified for use in membrane systems producing drinking water (ANSI/NSF Standard 60)

Uses

- Control of calcium carbonate, calcium sulfate, barium sulfate, calcium fluoride, silica, and hydroxides of iron and aluminum
- Can be blended with other pretreatment formulations from Professional Water Technologies to reduce chemical dosing equipment

Specifications

Appearance	Colorless/Amber
pH	1.80 – 2.80
Density (kg/liter)	1.05 – 1.15



Packaging

Pail: 5 gallon/18.9 liter

Tote: 275 gallon/1,040 liter

Drum: 55 gallon/208 liter

Bulk: available upon request

For special packaging options, please contact PWT or your local distributor.

SpectraGuard™ 105
LIQUID REVERSE OSMOSIS ANTISCALANT

SpectraGuard™ 105

LIQUID REVERSE OSMOSIS ANTISCALANT

General Mixing & Application Instructions for SpectraGuard™ 105

1. Typical dose rates are 0.2 to 1.2 mg/l.
2. Contact Professional Water Technologies™ or your local distributor for custom chemical dosing recommendation.
3. We use ProDose to determine your scaling potential and recommended chemical dosing levels.

ProDose XPRT™ – Scaling Prediction Software

ProDose XPRT™ uses the most accurate scaling prediction calculations available to accurately determine effective antiscalant dosage, and cleaning chemical usage. The user can enter multiple cases to study various operating conditions, directly enter concentrate analysis, and select the best PWT product and dosage for the application.

ProDose XPRT™ is available upon request only. Please contact your PWT representative for more information.

PWT ProDose

PWT

UNITS: US | TEMPERATURE: Fahrenheit | PERMEATE FLOW: 81.00 | RECOVERY: 75.0 % | ANTISCALANT: SpectraGuard Liquid | DOSAGE: 2.95 PPM | SOURCE: Well Water | PROJECT NAME: Project 1 | CASE: 1

PROJECT INFORMATION

OVERVIEW

CLIENT NAME: City of San Diego
PROJECT NAME: Project 1
LOCATION:
PREPARED BY:
DATE: 5/1/2016
WATER TYPE: Well Water

MEASUREMENTS

PRESET UNITS: CGS | Metric | U.S.
TEMPERATURE: Deg F
FLOW RATES: Gal/min
MASS UNITS: lb
Enter

TOTAL CASES (1 AVAILABLE) Max 9 +

Cases	Modified Date
1	5/27/2016

COMMENTS (OPTIONAL)

Selected Case Description